



Concrete Sealer

Solvent base sealer for concrete

Concrete sealer is a solvent-based coating that penetrates deeply and seals your surfaces against the absorption of water, oil and dust making it easier to clean. It protects your surface from tire marks, petroleum products, and calcium, among other things. The product will not flake or discolour and forms a translucent film when dried. Its special formulation provides long-lasting protection.



Advantages

- Excellent adhesion
- UV Resistant
- Wear Resistance

Functions

- Seal

Surfaces

- Concrete

Application temperature

- 10°C and more

Building components

- Paving

Application tools

- Spray gun
- Paint brush
- Roller

Service temperature

- 40°C to 85°C

Covering rate

- Smooth Surface : 7,5 to 12,5 m²/L 300 to 500 ft²/gallon
- Rough Surface : 3 to 4 m²/L 120 to 160 ft²/gallon

Colors

- Clear

Density

- 0,90 - 1,00

Surface preparation

- Surfaces must be clean and free of dust, dirt or other contaminants.



Application

Do not apply if rain is expected and/or if dew may occur before complete drying. Stir well all the contents of the pail before application. During the application and during the complete drying, the temperature should be above 10°C. Apply the product in 2 thin coats evenly over the entire surface, allowing about 20 minutes to dry between coats. Allow to dry and harden, protecting the surface against weathering. Close the container after each use.

Drying

Allow to dry and harden before allowing movement or repositioning of furniture.

Cleaning

Mineral spirits

Storage

The product may be kept in its original sealed container up to up to 12 months after the date of purchase by the user.

Format

3,78L / 18,9L

Restriction / Caution

Warranty

The customer shall verify of the suitability of this product for the intended purpose. Applicator's skill, weather and surface conditions being beyond manufacturer's control, we limit our liability to replacement of defective material only in sealed container, within 1 year of proof of purchase. FOB plant.



2645-B, boul. Terra-Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



www.condor.pro

DANGER



Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure. Central nervous system.

PRECAUTIONARY: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Keep container tightly closed. Ground/ bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Do NOT induce vomiting. **IF ON SKIN:** Take off immediately all contaminated clothing. Rinse skin with water or shower. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. **IN CASE OF FIRE:** Use dry chemical powders, CO₂, water spray (fog) or foam for extinction. Store in a well-ventilated place. Keep cool. Dispose of contents / container by a local waste disposal company according to regional regulations.