



Rubberized flashing cement - Wet and dry surface

Professional Selection

T325

Thiromo T325 is a new generation of rubberized plastic cement for wet and dry surfaces meeting the requirements of professionals and contractors. This product is used primarily to seal cracks, holes and to repair deteriorated areas on foundations, asphalt roofs, shingle flashings, vents and chimneys. This product has better strength and greater flexibility compared to regular plastic cements. The consistency of this product is designed to facilitate trowel application. It has excellent adhesion, good resistance to weather and temperature variations and forms a tough and waterproof coating once dry.



Advantage

- Professional selection
- 10 years warranty
- Dry or wet surfaces
- Enriched with rubber
- Multipurpose
- Resistant and flexible
- Easy application

Function

- Seal
- Repair

Building component

- Roofing
- Foundation

Surface

- Asphalt shingle
- Concrete
- Metal

Application tools

- Putty knife
- Trowel

Application temperature

Any temperature but it is easier to apply the product when it is temperate.

Service temperature

-40°C to 85°C

Covering rate

- 0,5 m2/kg applied 3mm thick
- 2 ft2/lbs applied 1/8" thick

Standard

CAN/ONGC 37.5-M89

Color

Black

% solid

93-97%

Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. Excess water should be removed, if possible, before application of T325.



Application

Do not apply if rain is expected. During colder periods, keep the product in a temperate place to facilitate its application. Apply an average thickness of 3mm (1/8in). To seal joints and cracks, press tightly to seal all gaps. To repair a larger crack, apply the Thiroco T325 to cover the damaged surface then place a reinforcement membrane and then apply another coat of Thiroco T325 over the entire patch. Close the container after each use.

Drying

Allow about 4h for surface drying and 48h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

Cleaning

Mineral spirits

Storage

The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

Format

13,6kg / 20kg

Restriction / Caution

Keep out of the reach of children. If the product is applied near a ventilation or air conditioning unit, take the necessary precautions to prevent infiltration of solvent odors toward the inside. Keep open container or freshly applied product away from open flames, sparks or other sources of heat. For outdoor use only.

Warranty

10 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid plant (FOB plant).

DANGER



Flammable liquid and vapour.

May be fatal if swallowed and enters airways. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONARY: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or a doctor. If exposed: Call a POISON CENTER or doctor/ physician. Get medical advice/ attention if you feel unwell.

IN CASE OF FIRE: Use water fog, foam, dry chemical or carbon dioxide. Do not use straight of water. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.



2645 B, boul. Terra Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474 6661



819 474 6681



www.condor.pro