



# Non-fiber and resaturating roof coating

## CR30

The CR30 is a non-fibrous coating for roofing. This product is used especially to waterproof concrete, wood, masonry, metal and asphalt roofs. Its application saturates again lightly damaged roofs. Once dried, the product forms a waterproof membrane that remains flexible to temperature fluctuations. It is ideal for all roof slopes. The presence of asphalt prevents the corrosion on the metal.



### Advantages

- Easy application
- Suitable for all roof angles
- Remains flexible in cold weather
- Do not react to moisture once dry
- Extends the service life of roofs

### Functions

- Waterproof
- Resaturate
- Regenerate

### Building components

- Roofing

### Surfaces

- Concrete
- Wood
- Masonry
- Shingle
- Metal

### Application tools

- Squeegee
- Brush
- Roller
- Spray gun
- Paint brush

### Application temperature

10°C and more preferably. The product will be thicker when the temperature decreases.

### Service temperature

-40°C to 85°C

### Covering rate

1,5 m<sup>2</sup>/L  
60 ft<sup>2</sup>/gallon

### Standard

CAN/ONGC 37-GP-6MA

### Colors

Black

### Density

0,9-1,0

### Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. Repair the surfaces with plastic cement from Condor.



#### Application

Do not apply if rain is expected. During colder periods, keep the product in a temperate place to facilitate its application. Stir well before application. Apply the product in an even layer. If the product is applied on a slope higher than 4/12, take the necessary precautions by applying a very thin layer to prevent slipping of the product until it completely dry. Close the container after each use.

#### Drying

Allow about 4h for surface drying and about 48h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

#### Cleaning

Mineral spirits

#### Storage

The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

#### Format

3,78L / 18,9L / 205L / Bulk

#### Restriction / Caution

Keep out of the reach of children. If the product is applied near a ventilation or air conditioning unit, take the necessary precautions to prevent infiltration of solvent odours toward the inside. Keep open container or freshly applied product away from open flames, sparks or other sources of heat. For outdoor use only.

#### Warranty

5 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid factory (FAB factory).



2645-B, boul. Terra-Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



[www.condor.pro](http://www.condor.pro)

### DANGER



Flammable liquid and vapour.

May be fatal if swallowed and enters airways. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

**PRECAUTIONARY:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

**IF SWALLOWED:** Do NOT induce vomiting. Immediately call a POISON CENTER or a doctor. If exposed: Call a POISON CENTER or doctor/ physician. Get medical advice/ attention if you feel unwell.

**IN CASE OF FIRE:** Use water fog, foam, dry chemical or carbon dioxide. Do not use straight of water. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.