



Fibered roof coating

Professional Selection

T40

The T40 is professional fibered coating for waterproofing foundations and roofs. The asphalt and mineral fibers contained in this product form a reinforced membrane that remains flexible. This product is strongly recommended for areas at risk of water infiltration or for places where the condition is uncertain. This product prolongs the life of damaged surfaces by regenerating them.



Advantage

Professional selection

10 years warranty

Easy application

Ideal for waterproofing areas with risk of infiltration

Better resistance due to the fibers

Does not flow

Remains flexible in cold weather

Extends the service life of roofs

Function

Waterproof

Saturated

Building component

Roofing

Foundation

Surface

Concrete

Wood

Masonry

Asphalt shingle

Metal

Application tools

Brush

Paint brush

Roller

Squeegee

Application temperature

10°C and more preferably. The product will be thicker when the temperature decreases.

Service temperature

-40°C to 85°C

Covering rate

1,5 m²/L

60 ft²/gallon

Standard

CAN/ONGC 37.8-M89

Color

Black

Density

0,90-1,0

Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. Surface repairs must first be done with plastic cement from Thi-ro-co.



Application

Do not apply if rain is expected. During colder periods, keep the product in a temperate place to facilitate its application. Stir well before application. Apply the product in an thin and even layer. If the product is applied on a slope higher than 4/12, take the necessary precautions by applying a very thin layer to prevent slipping of the product until it is completely dry. Close the container after each use.

Drying

Allow about 4h for surface drying and about 48h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

Cleaning

Mineral spirits

Storage

The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

Format

3,78L / 18,9L

Restriction / Caution

Keep out of the reach of children. If the product is applied near a ventilation or air conditioning unit, take the necessary precautions to prevent infiltration of solvent odors toward the inside. Keep open container or freshly applied product away from open flames, sparks or other sources of heat. For outdoor use only.

Warranty

10 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid plant (FOB plant).



2645 B, boul. Terra-Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474 6661



819 474 6681



www.condor.pro

DANGER



Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONARY: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or a doctor. **IF EXPOSED:** Call a POISON CENTER or doctor/ physician. Get medical advice/ attention if you feel unwell. **IN CASE OF FIRE:** Use water fog, foam, dry chemical or carbon dioxide. Do not use straight of water. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.