



# Sealflex Fibered and elastomeric roof coating

## CR4346

Sealflex Fibered and Elastomeric Roof Coating is a water-based emulsion used to waterproof asphalt shingle, wood, concrete, steel, EPDM or TPO membranes. It's also suitable for RVs. This product is highly recommended for areas with risk of water infiltration or for places where the condition is uncertain. In addition to waterproofing the surface, the product will give a new look to your roof and protect it from UV rays.



### Advantages

- 100% acrylic and odourless
- Enriched with fiber for optimal waterproofing
- Super Flexible
- Resists cracking and UV
- Fast drying
- Restores a new look to the surface
- Indoor and outdoor use

### Functions

- Repair
- Waterproof
- Paint

### Surfaces

- Asphalt shingles
- Steel
- Wood
- Concrete
- RV roof membrane
- EPDM and TPO membrane

### Application temperature

10°C and more

### Covering rate

1 m<sup>2</sup>/L (40 ft<sup>2</sup>/gallon)

### Building components

Roofing

### Application tools

- Paint brush
- Roller
- Trowel

### Service temperature

-40°C to 90°C



#### Colors

White

#### Density

1,2-1,3

#### Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. Clean the surface with a universal degreaser except asphalt shingles. Brush and rinse thoroughly to remove all traces of soap. Sand smooth surfaces for better adhesion. Using a high pressure machine may be useful in some cases. Use Sealflex Elastomeric Plastic Cement for big repairs and allow a 24-hour drying time before applying the product.

#### Application

Do not apply if rain is expected in the next 48 hours. Stir well before application. The product does not require any dilution. Try the product on a small surface to validate if the product is suitable. At the time of application and for complete drying, the temperature should be above 10 ° C. Ideal conditions are 25°C and 50% relative humidity. Avoid application in direct sunlight or on a very hot surface. To ensure good waterproofing and perfect finish, we recommend applying two coats. Apply a first layer always in the same direction (north to south). Allow sufficient drying time before applying the second coat. Obviously, the drying time varies depending on the application method, the temperature, the relative humidity and the thickness applied. On average, it is necessary to wait between 2 to 3 hours before the application of the second layer. Apply a second layer perpendicular to the first layer and always in the same direction (west to east). Protect the surface if drying is not complete before dew, if showers may occur. Close the container after each use.

#### Drying

Allow about 20-30 minutes for surface drying and 24-48h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

#### Cleaning

Water

#### Storage

Store this product away from frost. The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

#### Format

3,78L / 17L

#### Restriction / Caution



#### Warranty

5 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid factory (FAB factory).

## DANGER



May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

**PRECAUTIONARY:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

**IF EXPOSED:** Call a POISON CENTER or doctor/physician. Get medical advice/ attention if you feel unwell. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.



2645-B, boul. Terra-Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



[www.condor.pro](http://www.condor.pro)