

Clear roof coating CR2030

The CR2030 is an acrylic roof coating. Composed of thermoplastic polymers, it forms by drying a transparent film which protects the roofs from the harmful effects resulting of the formation of algae and mold. It also protects against coniferous spines. It has the characteristic of keeping in place the rocks of the shingles. It is ideal for extending the useful life of shingles but also RV roofs, tarred paper surfaces, cedar shingles and wood. This coating forms a flexible and durable coating that can withstands extreme temperature variations.



Advantages Odorless Translucent acrylic product Nontoxic Water repellent Protects against algae and mildew Easy application **Functions Building components** Protect coating Roofing Surfaces Application tools Tarred paperCedar shingle Spray gun Wood Paint brush Roller Asphalt shingle **RV** roofing

Application temperature 10°C and more for the next 24 hours Service temperature -40°C to 85°C

Covering rate

Standard

Smooth Surface : 7 to 12 m2/L 300 to 500 ft2/gallon Rough Surface : 3 to 4 m2/L 120 to 160 ft2/gallon

Colors Density 0,95-1,05 Clear

Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants. To stop organic contaminants, clean the surface using a biocide available at the hardware store. Repairs must first be made with Condor plastic cement.



Application

Do not apply if rain is expected and/or if dew may occur before complete drying. Stir well all the contents of the pail before application. During the application and during the complete drying, the temperature should be above 5°C. Apply a thin layer of the product evenly over the entire surface. Allow to dry and harden, protecting the surface against weathering. Close the container after each use.

Drying

Allow about 10 minutes for surface drying and about 1-5h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

Cleaning			
Water			
Storage			

Store this product away from frost. The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

Format

3,78L / 18,9L

Restriction / Caution

Do not apply on wet surfaces. Make sure the bituminous surfaces are stable and dry.

Warranty

5 years limited warranty when installed and / applied as recommended by the or manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid factory (FAB factory).



IF ON SKIN: Wash with plenty of water and soap. IF INHALED: Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. IF EXPOSED: Call a POISON CENTER or doctor/ physician. Call a POISON CENTER or doctor if you feel unwell. If eye irritation persists get medical advice/ attention. Store in a well ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.

