



CR-760 Condor-Bloc

Elastomeric Asphalt Emulsion Membrane

CR-760 Condor-Bloc is a polymer-enhanced, single-component asphalt emulsion membrane designed for below-grade waterproofing of foundation walls and other structures. Solvent free, it has excellent adhesion to most construction surfaces such as concrete, brick, wood, metal and stone. CR-760 can be applied in a single layer or multiple with reinforcement fabric.



Advantages

- Seamless elastomeric membrane
- Solvent free and environmentally friendly
- Very flexible
- Retain flexibility over a wide temperature range
- Excellent adhesion to most construction surfaces
- Can be applied to damp or green concrete
- Can be applied in one coat or multiple coats with reinforcing fabric

Functions

- Waterproof

Building components

- Poured and block foundation walls
- Insulated concrete forms
- Footing and split slab floors
- Retaining walls

Surfaces

- Concrete
- Asphalt Shingles
- Brick
- Metal
- Wood

Application tools

- Paint brush
- Roller
- Sprayer

Covering rate

- 0.141 L / m² (Roller)
- 134 m² (1442.4ft²) / 18.9L bucket
- (At temperature 20°C)

Standards : CAN/CGSB-37.3

Application temperature

- 10°C & above

Service temperature

- 40°C to 60°C

**Color**

Black (once dried)

Density & % Solids

D= 1,06

% Solids = 70%

Surface preparation

All surfaces must be sound, dry, clean and free of dust, dirt or other contaminants. Fill the formwork tie holes with mortar or bituminous roofing cement and allow to dry. The concrete surfaces must be free of sharp edges, voids or flaked areas.

Application

Do not undertake any work if rain is forecast or if the ambient and substrate temperatures are below 5°C within the next 24 hours. Stir well before application. The product does not require any dilution. Try the product on a small surface to validate if the product is suitable. At the time of application and for complete drying, the temperature should be above 10 ° C. Apply the product using a brush, roller or paint brush. Clean tools and equipments with mineral spirits after use. The covering rate may vary depending on the application method, the applicator' skills, the surface porosity and the temperature. One coat is sufficient, but if a second or more coats are desired, you must wait 15-30 minutes before applying the next coat. Protect the surface if drying is not complete before the dew falls, or if rain is likely to happen. Close the container after each use.

Drying

Sufficiently dry to walk on after approximately 30 minutes to 1-2 hours. Completely dry within 12 to 24 hours. Drying time depends on the application method, ambient temperature, surface area, and thickness applied.

Cleaning

Mineral Spirit

Storage

Store this product away from frost. The product can be kept in its original, tightly sealed container for up to 12 months after the date of purchase by the user.

Format

18.9L / 205L



Restriction / Caution

Keep out of the reach of children. If the product is applied near a ventilation or air conditioning unit, take the necessary precautions to prevent infiltration of odours toward the inside. Keep open container or freshly applied product away from open flames, sparks or other sources of heat. For outdoor use only.

Warranty

5 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid factory (FAB factory).

DANGER



May cause cancer. May cause damage to organs through prolonged or repeated exposure. May cause skin and eyes irritation. Harmful if swallowed. KEEP OUT OF REACH OF CHILDREN.

PRECAUTIONARY : Obtain the instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust / gas / mist / vapours & spray. Wash exposed and/or contaminated areas thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/clothing and eyes/face protection. Store locked up. Dispose of contents/container by a local waste disposal company according to regional regulations.

FIRST AID TREATMENT : Breathing exposure : move the person outside for fresh air. Get medical advice/attention if feeling unwell, or if coughing / others symptoms do not subside. Skin contact : Wash with cool water and a pH-neutral soap or a mild skin-friendly detergent. Do not use solvents. A gentle skin-friendly oil can also be used. Obtain medical advice if irritation or other more severe skin symptoms appear and persist. Eyes contact : Rinse with plenty of fresh water for at least 15 mins. Get medical attention immediately, do not try to remove the product from the eyes. If swallowed and the person is conscious, clean and rinse the mouth with plenty of water. Do not induce vomiting. Get medical attention immediately and/or contact a Poison Control Center.



2645-B, boul. Terra-Jet, Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



www.condor.pro